



ENCLOSURE (CONTAINING TERMINAL STRIP) ON 2M LEAD.
LEAD PROTECTED BY FLEXIBLE STEEL CONDUIT.
ENCLOSURE DIMS: 119 HIGH X 159 WIDE X 76 DEEP.

SIDE VIEW

FRESH AIR END VIEW

PLAN VIEW

SUPPLY AIR END VIEW

500mm x 350mm CLEARANCE
REQUIRED FOR ENCLOSURE
ACCESS (FRONT ACCESS).

500mm x 350mm CLEARANCE
REQUIRED
FOR CONTROL PANEL ACCESS
(CONTAINING TREND IQ422 CONTROLLER)
(BOTTOM ACCESS).

300mm x 900mm CLEARANCE
REQUIRED FOR FRESH AIR
FILTER ACCESS
(BOTTOM ACCESS).

900mm x 200mm CLEARANCE
REQUIRED FOR RETURN AIR
FILTER ACCESS
(BOTTOM ACCESS).

- NOTES:
1) HANGING POSITIONS HAVE 9mm DIA HOLES (X8)
2) RECTANGULAR SPIGOTS HAVE MEZ.20 FLANGES FITTED

REVISION	REASON FOR REVISION	INITIALS	DATE	DRAWING No: VHR500VHR600LHABCDTREND		
REV A				DRAWING DESCRIPTION: VHR500-VHR600 LEFT HAND CONFIGURATION A,B,C,D WITH TREND IQ422 CONTROLLER		
REV B				QUOTE No AND NAME: NA		
REV C				DRAWN BY: PJT	DATE: 13/03/18	SCALE: 1:25 @ A4
				DIMENSIONS: mm		

